



Compact > [Cloud Gateway Max](#)

Cloud Gateway Max

UCG-Max

- Datasheet**
- In The Box
- Marketing Images
- Accessories
- Installation Guide



Overview

Dimensions	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
UniFi Application Suite	
Network	✓
Protect	✓
Access	✓
Talk	✓
Connect	✓
Managed UniFi Devices	30+
Managed Cameras	(15) HD (8) 2K (5) 4K
Managed Access Hubs	50
Simultaneous Users Connected	300+
Max. WAN Port Count	4
Default WAN Ports	(1) 2.5 GbE RJ45
Port Layout	
2.5 GbE RJ45	5 (2.5G/1G/100M/10M)
IDS/IPS Throughput	2.3 Gbps
Form Factor	Compact desktop

Security

Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Zone-Based Firewall Advanced Filtering (Regions, Domains, Apps)	✓
Content Filtering	✓
Intrusion Prevention (IPS/IDS)	✓
Ad Blocking	✓
IDS/IPS Signatures	55,000+ with CyberSecure
VLAN/Subnet-based Traffic Segmentation	✓

VPN & SD-WAN

License-Free SD-WAN	✓
Site-to-Site VPN	
Site Magic	✓
IPsec	✓
OpenVPN	✓
VPN Server	
Identity Endpoint One-Click VPN	✓
Teleport Zero-Configuration VPN	✓
WireGuard	✓
OpenVPN	✓
L2TP	✓
VPN Client	
OpenVPN	✓
WireGuard	✓

Networking

Multi-WAN Load Balancing	✓
Dynamic Routing	
OSPF	✓
Advanced QoS	✓
Multicast DNS (mDNS)	✓
Advanced NAT (SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT)	✓
Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
Additional Internet Failover with UniFi LTE Backup	✓
Internet Quality and Outage Reporting	✓
MAC Address Table Size	2,000
Policy-based WAN and VPN Routing	✓
Customizable DHCP Server	✓
IPv6 ISP Support	✓
IGMP Proxy	✓
Virtual Network Override	✓
All Traffic Flows	✓

Hardware

NVR Storage	Selectable NVMe SSD up to 2 TB
Max. Power Consumption	16.1W
Power Method	USB type C (5V DC/5A)
Power Supply	USB type C (5V DC/5A) (Adapter included)
Supported Voltage Range	100-240V AC
Heat Dissipation	55 BTU/hr
Processor	Quad-core ARM® Cortex®-A53 at 1.5 GHz
System Memory	3 GB
Weight	Without SSD: 460 g (1 lb) With SSD: 519 g (1.1 lb)
Enclosure Material	Polycarbonate
LCM Display	0.96" status display
Management	Ethernet Bluetooth
LEDs	
Ethernet	✓
Button	(1) Factory reset
ESD/EMP Protection	Air: ± 8kV, contact: ± 4kV
Ambient Operating Temperature	-10 to 40° C (14 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 09004-24-08356, SRRC

Software

Application Requirements	
Mobile App	UniFi iOS™ and Android™: Version 10.17.2 and later

Company

- Blog
- Case Studies
- Careers
- Trust Center
- Contact Us
- Investors
- Compliance

Training

- Courses
- Calendar
- Trainers
- Become a Trainer

Buy Now

- Ubiquiti Store
- Find a Distributor
- Become a Distributor

Tools

- WiFiman
- UISP
- UniFi Design Center
- UISP Design Center
- Downloads

Stay in Touch

[Subscribe](#)

